



TECHNICAL DATA SHEET

Noelle Industries, Inc.
Adhesives • Coatings • Conductives • Encapsulants

NOELLE E903-54-3

A One Component Electrically Conductive Ink

Description:

Noelle E903-54-3 is a silver filled, electrically conductive, one component high performance screen printable, thermoplastic ink. Noelle E903-54-3 offers a slower drying time than Noelle E903-52 for improved production throughput.

Advantages:

Noelle E903-54-3 features high electrical conductivity and has a desirable viscosity for screen printing or dot dispensing.

Physical Properties:

Color: Silver
Specific Gravity 1.59
Coverage (Wet thickness) 167 cm² / gram / 0.001

Shelf Life: (Sealed container)

One Year @ 25°C

Chemical Properties:

Solvents used is Ethyl Acetate, Methyl Ethyl Ketone and PM Acetate

Dry time:

Longer times or higher temperatures will further enhance end properties.

Dry Temp:	90°C	120°C
Dry Time (Minutes)	20	5

Properties:

Sheet Resistivity, @ 25°C (Ohm / Sq / Mil): <0.0015
@ 90°C After 120 minutes: <0.0010

All values reported above are typical values, and are reported as a means of reference. Individual testing should be done to determine actual results, tested at specific conditions.

• 76 Treble Cove Road, Building # 3, Unit C, North Billerica, MA 01862

• Phone: (978) 439-9841 • Fax: (978) 439-9842 • Website: www.noelleindustries.com • email: info@noelleindustries.com